



NUC-APL-Slim

Intel® Apollo Lake Fanless NUC Slim System



- > Onboard Intel® Celeron® Processor J3455/N3350
- > Single DRAM Socket, Max. Up to 8GB DDR3 1866MHz
- > Rich I/O, 1 x COM, 2 x HDMI, 2 x LAN, 4 x USB3.0, 1 x Audio, 2 x Antenna Mounting
- > Expansion Slot, M.2 Key-B, M.2 Key-E
- > Fanless Operating from 0°C ~ 50°C
- > DC Power Input +12V
- > Compact Size, 115mm x 111mm x 45mm
- > Supports VESA/Din-Rail Kit
- > TPM 2.0 (Factory Option)

+ Spec

System	
Processor	Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz) Intel® Celeron® Processor N3350 (2M Cache, up to 2.4 GHz)
System Memory	1 x 204-pin SO-DIMM Socket, Max, Up to 8GB DDR3L 1866MHz
BIOS	AMI BIOS, 128Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU Temperature, Voltage with Auto Throttling Control
SBC	NCM-APL
Expansion	
Expansion	1 x M.2 (Key-B, 2242/3042, PCIe, SATA, USB 3.0, USB 2.0) 1 x M.2 (Key-E, 2230, PCIe, USB2.0)
Storage	
Solid State Drive	1 x M.2 (Key-B, 2242, SATA)
I/O	
USB	4 x USB 3.0 (5Gbps)
COM Port	1 x RS-232/422/485 (BIOS&Cable)
Antenna	2 x Antenna Mounting with Dust Cover
External I/O	
Audio Port	1 x Audio Jack (Mic-in + Line-out Combo)
System Control	
LED Indicator	1 x Power on/off LED & Storage Access LED on front side
Display	
Chipset	Intel® HD Graphics 500
Resolution	2 x HDMI 1.4b: Max. Resolution 3840x2160@30Hz *1 x DP/DVI-I/VGA (Factory Option): Max. Resolution 1920 x 1080@60Hz *DP/DVI-I/VGA is an option which will replace the location of COM.
Multiple Display	Dual Display
Audio	
Chipset	Realtek ALC892
Ethernet	
Chipset	Realtek RTL8111E Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx Gigabit Ethernet Compatible
LAN Port	2 x RJ45
Mechanical & Environmental	
Power Requirement	+12V
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 5.0 Compliant
Power Type	AT/ATX (ATX is default setting)
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F) with 0.2m/s air flow -10°C ~ 50°C (14°F ~ 122°F) with 0.5m/s air flow
Storage Temperature	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.72KG (1.59lbs)
Construction	Aluminum + Metal
Mounting Kit	VESA/Din Rail Kit
Dimension (L x W x H)	115mm x 111mm x 45mm (4.53" x 4.37" x 1.77")
Vibration Protection	With SSD: 5Grms, IEC 60068-2-64, Random, 10 ~ 500Hz, 30min/Axis, 3 Axis
Shock Protection	With SDD : 55G, IEC 60068-2-27, Half Sine, 11ms, Z Axis



Drop	ISTA 2A, IEC-60068-2-32 Test : Ed, 1 Corner, 3 Edges, 6 Faces
Certifications	
Certification Information	CE, FCC Class A
Software Support	
OS Information	Win 10, Linux
Power Requirement	
Adapter	Input: 100 ~ 240Vdc/ 50 ~ 60Hz Output: 12V/5A AC-DC 60W Adapter

+ Ordering

NUC-APL-34-A1-2R
Intel® Celeron® Processor J3455 Fanless NUC Slim System
NUC-APL-33-A1-2R
Intel® Celeron® Processor N3350 Fanless NUC Slim System