



RAYSTAR

曜凌光電股份有限公司 Raystar Optronics, Inc.

Web: www.raystar-optronics.com E-mail: sales@raystar-optronics.com

RFA6400E-AWW-MNN

SPECIFICATION

General Specifications

- Size: 4.0 inch
- Dot Matrix: 480 × 3(RGB) × 480 dots
- Module dimension: 78.8(H) × 82.95 (W) × 4.77 mm
- Active area: 71.856(H) × 70.176 (V) mm
- Dot pitch: 0.1497(H) × 0.1462(V) mm
- LCD type: TFT, Normally Black, Transmissive
- View Direction: 80/80/80/80
- Aspect Ratio: 1:1
- Interface: 2-Lanes MIPI
- Driver IC: ST7701S
- Backlight Type: LED ,Normally White
- Touch Panel: Without Touch Panel
- Surface: Glare


*Color tone slight changed by temperature and driving voltage.

Interface

LCM PIN Definition

Pin	Symbol	Function
1	GND	Power ground
2-5	NC	No connect
6	GND	Power ground
7	D0N	MIPI DSI differential data pair (Data lane 0)
8	D0P	
9	GND	Power ground
10	CLK_N	MIPI DSI differential clock pair
11	CLK_P	
12	GND	Power ground
13	D1N	MIPI DSI differential data pair(Data lane 1)
14	D1P	
15	GND	Power ground
16	IOVCC	I/O and interface power supply (1.8V)
17	RESET	Reset input
18	TE	Tearing effect output pin.
19	VCI	Analog power supply
20	VCI	Analog power supply
21	NC	No connect
22	VLED-	Power for LED backlight cathode
23	VLED+	Power for LED backlight anode
24	GND	Power ground

Contour Drawing



Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-30	—	+80	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Typical Operation Conditions

Item	Symbol	Values			Unit
		Min.	Typ.	Max.	
Interface Supply Voltage	VCI	2.5	2.8	3.6	V
Power voltage	IOVCC	1.65	1.8	3.3	V
Current for Driver(White)	IDD	-	11	16.5	mA

Backlight Driving Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current	ILED	-	100	-	mA
LED voltage	VLED+	10.8	12.4	13.6	V
LED Life Time		50,000	-	-	Hr